No-Harm List

Flow Improvers (BDFI)

for FAME as blend component in Diesel fuel

As by: 18.05.2020

The no-harm test for flow improvers for FAME as blend component in Diesel fuel comprises the following test criteria:

- Minimum requirements (B100)
- XUD9 test according to CEC F-23-1-01 (nozzle fouling)
- DGMK filtration test 663
- Check of compatibility with engine oil (derived from DGMK 531-1)
- Corrosion test
- Foam test
- Emulsion test

The no-harm tests are carried out with B10 blends (10% (V/V) FAME in diesel fuel) and all requirements of the test must be met at a dosage rate recommended by the producer. The maximum dosing rate however is 1.0% (w/w). Products that fulfil all criteria of the no-harm test are published in this no-harm list of Association Quality Management Biodiesel (AGQM). Additional information can be found on the website (www.agqm-biodiesel.com).

Since the development of the first no-harm tests, test methods and techniques for testing quality properties have developed further or have been newly developed. In order to take this technical progress into account and to meet future requirements and challenges with the no-harm test, all products that have successfully passed the no-harm test must be tested again every 5 years if the no-harm test procedure changes significantly. Significant changes include, for example, newly developed test methods that replace methods from the no-harm test, higher requirements due to changes in the limit values or the implementation of new parameters that are necessary to ensure the no-harm properties of a product. Products that have not been retested will be removed from the no-harm list.

AGQM carried out the project with the greatest possible scientific accuracy and care. Nevertheless, no guarantee can be given for the correctness, completeness and topicality of the content provided. For this reason, we exclude any liability in connection with the use of the no-harm list. It is recommended to obtain the information directly from the manufacturer.

All rights reserved. Translations, partial reprints or any other type of reproduction, including inclusion in electronic databases and duplication on data carriers, only allowed with the written permission of AGQM.

Overview of the successfully tested Biodiesel Flow Improvers

| Reg. no. | Filed | Company | Brand name | Test level |
|------------|------------|---------------|-------------|------------|
| 2020-FI-01 | 18.05.2020 | CHIMEC S.p.A. | CHIMEC 6830 | B10 |
| 2020-FI-02 | 18.05.2020 | CHIMEC S.p.A. | CHIMEC 6043 | B10 |

